



# MODEL 6170H

Wall Mount
Garage Door Opener
Battery Backup Capable

PROFESSIONAL LINE



# Highlights

- Wall Mount Design
  - Cleaner Look Eliminating the rail and opener from the ceiling brings a clean and open look to your garage. Enjoy the view or use the freed-up space for storage or other purpose.
  - » Compact Compact design fits into tight side room spaces between track and wall.
  - » Headroom Ideal for garages with beam obstructions which prevent installation of a traditional opener.
  - » Safe-T-Pulse<sup>TM</sup> Patent-pending pulsing action provides safety check before closing and eliminates the need for an external cable tension monitoring device.
- Quiet, Powerful Performance 24 Volt DC motor provides maximum power to operate doors up to 850 lbs\* at a speed of 7.5" per second\*\*.
- Battery Backup (Model 6170H-B) Don't get locked outside the garage when the power goes out! Battery backup is included.
- GenieSense<sup>™</sup> Monitoring and Diagnostic Technology Provides safety by continuously monitoring operation of the door, stopping the operation to alert you when significant changes occur.

- Soft Start and Stop Control DC technology allows your door to begin and end its movement smoothly instead of abruptly whenever you operate it, creating less noise and less wear on the door.
- Smart Lighting Bright LED light fixture with the flexibility to place wherever desired in the garage.
- Dependability The quality built into a Model 6170H is backed by a Limited Lifetime Warranty<sup>6</sup> for the motor.
- Smart Garage Capabilities
  Integrated Wi-Fi provides multiple benefits such as:
  - intogratou vvi i i providoo manapio bononto caon do
  - » Security Instantly know if someone is operating your garage door without permission
- Convenience Open your door for family members, deliveries, service providers or provide them their own virtual key from anywhere with your smart device!
- » Safety Have garage door automatically close at a specific time or after an elapsed time period in case it's left open.



\*\* Operating speed may vary based on cable drum selection and application.

Limited non-transferable warranty. See Programming, Operation and Maintenance manual for details

THE GENIE STORY: Genie has a rich history in developing garage door openers that feature reliability, strength, safety, security, and convenience. Since 1954, Genie has produced millions of openers that serve millions of satisfied homeowners every day of every year. Shouldn't you have one in your garage? Genie — The Brand You Trust.





# Wall Mount Pro Series MODEL 6170H



# **Standard Equipment and Warranty**





















## POWER AND CONTROL

**DC Motor Smart Technology** – The DC motor provides quiet operation as well as Soft Start and Stop control. This means the door begins and ends its travel smoothly, not abruptly, which lessens noise as well as wear and tear on the garage door.

**Wall Mount Design** – Eliminates the traditional rail and powerhead design by attaching directly to the garage door's spring tube. This allows for a cleaner garage ceiling, and frees up space for additional storage and headroom. Beneficial for installing in garages with beam obstructions. Powerful yet compact size allows for more placement options, especially in tight spaces next to the garage door.

**Speed** – Opening speed of 7.5 inches/second\* gets you on your way faster.

#### **SAFETY**

Safe-T-Beam® Non-Contact Reversing System – Puts an invisible beam across the door opening. The door stops and reverses to open position if anything passes through the beam.

Genie Exclusive Safe-T-Pulse™ System – Patent-pending system that provides internal tension monitoring of door cables with an electronic pulse during initial door travel. If it detects slack or unspooled cables, the system will stop unsafe operation. Internal slack cable detection cannot be bypassed or improperly aligned like external slack cable detection methods.

### **SECURITY**

IntelliCode® Access Security System – Superior encryption technology (also known as rolling codes) that prevents piracy of the radio signal that opens your garage door by continually seeking a new code from billions of combinations.

**Electric Lock** – Automatically locks door after closing to safeguard your garage.

#### CONVENIENCE

Auto-Seek Dual Frequency – The opener automatically uses either 315 or 390 MHz frequency to avoid potential nearby interference, such as military base equipment, to help ensure the opener operates properly.

**Pre-Programmed Remote** – Ready to use out-of-the-box with simple steps to change the programming if so desired.

HomeLink® and Car2U® Compatibility – Works with ALL HomeLink and Car2U systems regardless of when those systems were made. No additional external repeater box or compatibility bridge needed.

**Wireless Wall Console** – An attractive wall console that's completely wireless for flexible placement in the garage. Features an optional pulsing back-light as well as delay button that gives ample time (up to 30 seconds) to exit the garage before the door begins moving. The work light button can turn just the opener's light on at any time. Compatible with most Genie Intellicode® openers made since 2013.

**LED Light Fixture** – Light fixture provides bright glowing light plus flexibility to place fixture wherever desired in the garage.

Battery Backup (Model 6170H-B) — No more unexpectedly getting locked outside the garage when the power goes out!





\*Operating speed may vary based on cable drum selection and application.

◊ Limited non-transferable warranty. See Programming, Operation and Maintenance manual for details.













# The Genie Company • One Door Drive, Mt. Hope, Ohio 44660 1.800.35.GENIE (354-3643) • www.geniecompany.com Item G001 6170 11/20

# Opener mounts to either side of door! Shown with optional battery backup (6170H-B)

# Aladdin Connect® INTEGRATED Wi-Fi CONNECTIVITY

Remotely monitor and control your garage door from almost anywhere with your smart device. Time-based features allow you to set door to automatically close and/ or notify after a set length of time; as well as schedule a specific hour and minute to close the door and/or notify when it does. Also allows for multiple individual user accounts so you can provide virtual key access for your garage door to a friend, relative, or service person for a certain time, a range of time, or permanently.



e Hey Google alexa ALARM.COM brilliant

Use the Aladdin Connect app to control any combination of 20 different Genie Wi-Fi integrated garage door openers Control or standalone Aladdin Connect Door Control Modules.

# YONOMI

# Convenience Options

# Wireless Keypad

Easy-to-program keypad mounts outside your door to give you convenient code access to your garage, which is great when you are outside without the remote control. Back-lit keypad lets you easily see the numbers and control up to 3 openers. Uses Auto-Seek Dual Frequency (315/390 MHz).



Choose a color for the flip-up cover that best complements your home. White is standard, other colors sold separately.



# 1-Button Remote

Simple yet versatile one-button remote features auto-seek dual frequency. Can be used on a keychain or as a traditional visor style remote. Backward compatible with all Intellicode® equipped Genie garage door openers.



#### TorqueMaster® Adapter Kit

Allows the Wall Mount opener to be installed on TourqueMaster springs without disassembly of the spring system.

### **Alternate Mounting Kit**

Chain and sprocket coupling kit allows the Wall Mount opener to be installed above or below the door shaft in applications with obstructions.

#### **Power Extension Kit**

Allows installation and full power up to 30' from opener when there is not a power outlet within 5-1/2'.



CALIFORNIA RESIDENTS – This opener has the option to add battery backup. As required by SB-969, all newly installed openers must have battery backup as of 7/1/19. To order this opener with battery backup, refer to Model 6170H-B. If needed, visit www.geniecompany.com or ask your Genie dealer for details.

YOUR GENIE PROFESSIONAL DEALER:

